

## SENCITY® OMNI-S stick antenna 1399.17.0232

### Description

Omni - directional multiband antenna for GSM 1800, GSM/PCS 1900, UMTS, LTE 2300, 2500 and 2600,  
 Also WLAN IEEE 802.11 b/g WiFi 2400 to 2500 MHz  
 Gain 2 dBi, vertical polarized antenna  
 Ingress protection IP67 (IEC 60529)  
 For outdoor and indoor applications  
 Pole or wall mount



### Product Configuration

#### Technical Data

##### Electrical Data

	Band 1
Frequency (MHz)	1710 - 2690
VSWR	1.8
Impedance (Ohm)	50
Gain (dBi)	2
3dB beamwidth (h) (°)	360
3dB beamwidth (v) (°)	65
Composite power max (W)	25
Ambient temperature (°C)	25

##### Ports

	Port 1
Connector	N, jack (female)
Polarization	vertical
DC grounded	Yes

##### General Data

IMD level 145 dBc at carrier power 2x 30dBm

##### Mechanical Data

Dimensions (mm) 120 x 22 (Height x Diameter)  
 Weight (kg) 0.3

INCLUDED MOUNTING MATERIAL: Bracket 9091.99.0173 and 2 metal-bands for mast-diameter 25mm - 101mm, all piece parts made of stainless steel

##### Environmental Data

Environmental conditions indoor/outdoor  
 Operation temperature (°C) -40 to 85  
 Storage temperature (°C) -55 to 85  
 Transport temperature (°C) -40 to 85  
 IP rating IP67  
 RoHS 2011/65/EU compliant  
 Lead-free soldered yes  
 WEEE 2012/19/EU special marking needed  
 REACH 2006/1907/EC compliant

LOW TEMPERATURE: IEC 60068-2-1 72h -55°C  
 HIGH TEMPERATURE: IEC 60068-2-2 72h +85°C  
 HUMIDITY: ETSI EN300-2-4 T4, 1E 144h 95%

## SENCITY® OMNI-S stick antenna 1399.17.0232

SALT SPRAY: EN 60068-2-11 / GB-T 10125 96h

MECHANICAL SHOCK: IEC 60721-3-4, 4M5

VIBRATION: IEC 60721-3-4 30 min/axis random 4M5

### Material Data

Radome colour	RAL 9003 (signal white)
Radome material	Glass Fibre

### Related Products

9091.99.0173 L - bracket for omni stick antennas

### Related Documents

Mounting instruction	DOC-0000296554
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00285540
3D-model	DOC-0000684122

### Additional Information

Mounting accessory included