

SENCITY® Omni-S 3x3 MIMO Antenna 1399.35.0002

Description

Small omni-directional MIMO indoor antenna for WiFi applications.
 Supports the 2.4 GHz and 5 GHz bands.
 Rugged design, meets EN 50155 railway standard.
 Fire retardant acc. to DIN 5510-2, BS 6853, EN 45545-2, NFPA130
 3x3 WiFi dual-band MIMO antenna with three ports QMA (female)



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2
Frequency (MHz)	2400 - 2690	5150 - 5935
VSWR	1.5	1.5
Impedance (Ohm)	50	50
Gain (dBi)	4	6
3dB beamwidth (h) (°)	360	360
Composite power max (W)	40	30
Ambient temperature (°C)	25	25
Port Isolation (dB)	20	20

Ports

	Port 1	Port 2	Port 3
Port name	WiFi 1	WiFi 2	WiFi 3
Connector	QMA, jack (female)	QMA, jack (female)	QMA, jack (female)
Polarization	vertical	vertical	vertical
DC grounded	Yes	Yes	Yes

Connections

	Band 1	Band 2
Port 1	X	X
Port 2	X	X
Port 3	X	X

General Data

Mechanical Data

Dimensions (mm) 31 x 91.8 x 281.8 (Height x Width x Depth)
 Weight (kg) 0.32

Low corrosion design acc. to MIL-F-14072(E).

Environmental Data

Environmental conditions indoor
 Operation temperature (°C) -40 to 85
 Storage temperature (°C) -40 to 85
 Transport temperature (°C) -40 to 85
 IP rating IPX5
 Flammability rating UL 94-V0
 RoHS 2011/65/EU compliant
 REACH 2006/1907/EC compliant

SENCITY® Omni-S 3x3 MIMO Antenna **1399.35.0002**

Flammability rating: DIN 5510-2, BS 6853, EN 45545-2, NFPA130

High-voltage-protection: Designed acc. to UIC 533

Environmental compliance: EN50155:2007

Material Data

Radome colour	RAL 7044 (grey)
Radome material	PC (Polycarbonate)
Back plate/base plate material	Aluminium

Related Documents

Mounting instruction	DOC-0000333282
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00180748
3D-model	DOC-0000353495

Additional Information

Some documents are related to the similiar antenna type 1399.35.0001.